

TECHNISCHE SPECIFICATIES


KABELSCHOENEN



Ratering
technische groothandel


KABELSCHOENEN

VLAKSTEEKHULSEN




kabel	type	kleur	dikte	b	l1	l2
0,5 - 1,0	820/1	■	0,5	2,8	17,5	8,0
	820/1A	■	0,8	2,8	17,5	8,0
	820/2	■	0,5	4,8	18,0	6,0
	820/3	■	0,8	4,8	18,0	6,0
	720	■	0,8	6,3	22,0	7,5
	720/8	■	0,8	7,7	25,0	9,5
	830/1	■	0,5	2,8	18,0	8,0
	830/1A	■	0,8	2,8	18,0	8,0
1,5 - 2,5	830/2	■	0,5	4,8	18,0	6,0
	830/3	■	0,8	4,8	18,0	6,0
	730	■	0,8	6,3	21,0	7,4
	730/8	■	0,8	7,7	25,0	9,5
	850/3	■	0,8	4,8	23,0	7,5
4,0 - 6,0	750	■	0,8	6,3	21,0	7,5
	750/9	■	1,2	9,5	26,5	12,0

VLAKSTEKERS



kabel	type	kleur	dikte	b	l1	l2
0,5 - 1,0	820/1C	■	0,5	2,8	22,0	11,5
	820/1B	■	0,8	2,8	14,6	5,5
	820/2B	■	0,5	4,8	22,0	11,5
	820/3B	■	0,8	4,8	22,0	11,5
	820	■	0,8	6,3	22,0	8,0
	830/2B	■	0,5	4,8	22,0	11,5
	830/3B	■	0,8	4,8	22,0	11,5
	830	■	0,8	6,3	22,0	8,0
1,5 - 2,5	850/2B	■	0,5	4,8	24,5	10,5
	850/3B	■	0,8	4,8	24,5	10,5
4,0 - 6,0	850	■	0,8	6,3	22,0	8,0

VLAKSTEEKHULSEN




kabel	type	kleur	dikte	b	l1	l2
0,5 - 1,0	820/1V	■	0,5	2,8	19,0	5,5
	820/1AV	■	0,8	2,8	19,0	5,5
	820/2V	■	0,5	4,8	20,0	7,0
	820/3V	■	0,8	4,8	20,0	7,0
	720/V	■	0,8	6,3	21,0	7,5
	830/1V	■	0,5	2,8	20,0	8,0
	830/1AV	■	0,8	2,8	20,0	8,0
	830/2V	■	0,5	4,8	20,5	7,0
1,5 - 2,5	830/3V	■	0,8	4,8	20,5	7,0
	730/V	■	0,8	6,3	21,0	7,5
	850/2V	■	0,5	4,8	20,5	9,5
4,0 - 6,0	850/3V	■	0,8	4,8	20,5	9,5
	750/V	■	0,8	6,3	25,5	11,5

VLAKSTEKERS




kabel	type	kleur	b	l1	l2
0,5 - 1,0	720AZ	■	6,3	22,0	7,5
1,5 - 2,5	730AZ	■	6,3	22,0	7,5
4,0 - 6,0	750AZ	■	6,3	22,0	8,0

RONDSTEKERS




kabel	type	kleur	b	l1
0,5 - 1,0	1020	■	4	22,0
1,5 - 2,5	1030	■	5	22,0
4,0 - 6,0	1050	■	5	22,0

RONDSTEKERS




kabel	type	kleur	b	l1
0,5 - 1,0	1020V	■	4	25,0
1,5 - 2,5	1030V	■	5	25,0
4,0 - 6,0	1050V	■	5	27,0

PENSTEKERS




kabel	type	kleur	d	l1	l2
0,5 - 1,0	705	■	1,9	22,0	10,0
1,5 - 2,5	710	■	1,9	23,0	10,0
4,0 - 6,0	715	■	1,9	26,0	11,0

OOGKABELSCHOENEN



kabel	type	kleur	d	l1
0,5 - 1,0	620/3	■	3,2	16,5
	620/4	■	4,3	17,5
	620/5	■	5,3	18,5
1,5 - 2,5	630/3	■	3,2	17,5
	630/4	■	4,3	18,5
	630/5	■	5,3	20,5
	630/6	■	6,5	22,5
4,0 - 6,0	630/8	■	8,4	23,5
	650/4	■	4,3	18,5
	650/5	■	5,3	21,5
	650/6	■	6,5	22,5
4,0 - 6,0	650/8	■	8,4	25,4
	650/10	■	10,5	27,5

RONDSTEEKHULSEN




kabel	type	kleur	b	l1
0,5 - 1,0	920	■	4	22,0
1,5 - 2,5	930	■	5	22,0
4,0 - 6,0	950	■	5	22,0

STOOTVERBINDERS



kabel	type	kleur	b	l1	l2
0,5 - 1,0	670	■	1,6	25,0	15
1,5 - 2,5	680	■	2,3	25,0	15
4,0 - 6,0	700	■	3,6	27,0	15

VORKKABELSCHOENEN




kabel	type	kleur	b	l1
0,5 - 1,0	620/C3	■	3,2	16,5
	620/C4	■	4,3	17,5
	620/C5	■	5,3	18,5
1,5 - 2,5	630/C3	■	3,2	17,5
	630/C4	■	4,3	18,5
	630/C5	■	5,3	20,5
	630/C6	■	6,5	22,5
4,0 - 6,0	650/C4	■	4,3	18,5
	650/C5	■	5,3	21,5
	650/C6	■	6,5	22,5
	650/C8	■	8,4	25,4
4,0 - 6,0	650/C10	■	10,5	27,5

STOOTVERBINDERS KRIMPKOUS




kabel	type	kleur	d	l1	l2
0,5 - 1,0	670WS	■	1,6	36,0	15
1,5 - 2,5	680WS	■	2,3	36,0	15
4,0 - 6,0	700WS	■	3,4	41,0	15

RONDSTEEKHULSEN



kabel	type	kleur	b	l1
0,5 - 1,0	920V	■	4	24,0
1,5 - 2,5	930V	■	5	24,0
4,0 - 6,0	950V	■	5	27,0

PARALLELVERBINDERS



kabel	type	kleur	b	l1	l2
0,5 - 1,0	770	■	1,6	17,0	7
1,5 - 2,5	780	■	2,3	17,0	7
4,0 - 6,0	790	■	3,6	21,0	7

Bron: Klauwe